

## Fluoride, Chloramines, Chlorine, VOC's, Lead, and Heavy Metals

AquaMetix® is a proprietary matrix comprising of at least two types of activated carbon, combined with proprietary Zeolite minerals, structurally bound with polymers into a highly porous block filter



AquaMetix® combines the highest FDA-compliant raw materials, with cutting-edge manufacturing methods resulting in unparalleled performance in an exclusively U.S.A. Manufactured product.

**MADE IN USA**

	Chloramines	VOC's	Chlorine	Lead	Mercury	MTBE	Pharmaceuticals	Fluoride
Overall %	>99%	94%	>99%	>99%	>98%	92.2%	96.1%	93%
Reduction	Reduction	Reduction	Reduction	Reduction	Reduction	Reduction	Reduction	Reduction
CF-AMB-975	3500 gallons	1400 gallons	+3500 gallons	3500 gallons	4000 gallons	800 gallons	1500 gallons	1000 gallons
CF-AMB-20	7000 gallons	2800 gallons	+7000 gallons	7000 gallons	8000 gallons	1600 gallons	3000 gallons	2000 gallons
CF-AMB-BB-10	10700 gallons	4200 gallons	+10700 gallons	10700 gallons	10700 gallons	2400 gallons	4500 gallons	3000 gallons
CF-AMB-BB-20	20700 gallons	8400 gallons	+20700 gallons	20700 gallons	20700 gallons	4800 gallons	9000 gallons	6000 gallons
Certified Test Protocol	Standard 42	Standard 53	Standard 42	Standard 53	Standard 53	Standard 53	Standard 401	Standard 53 Modified (1 ppm) Challenge
Lab	IAPMO	Pace Analytical	Pace Analytical	IAPMO	IAPMO	IAPMO	QFT	QFT

These filters are not intended to be used where the water is microbiologically unsafe or with water of unknown quality without adequate disinfection before or after the filter.  
Maximum operating temperature 100°F; Maximum operating pressure 100 psi.

All performance claims presented here are based on data believed to be reliable but are not to be considered a warranty of performance.

Performance of the filter may be altered by the housing, or the source water's organic content, turbidity, pH, or other conditions encountered in actual use.